

INTRODUCTION OF PETROCHEMICAL PRODUCTS

GENERAL PURPOSE POLY STYRENE (GPPS)

1460

GPPS / TABRIZ Pet.Co.

DATASHEET	VALUE	UNIT	TEST CONDITIONS	TEST METHOD
Density	1.04	g/cm ³	-----	ASTM D955
MFI	6.5	g/10 min	At 5Kg, 200°C	ASTM D1238
Styrene Residual Monomer	< 500	PPM	-----	CLG LABPSG004
Vicat Softeing Point	103	°C	50 °C/hr 1kg	ASTM D1525
Rockwell Hardness	SCALE/ L70	-----	-----	ASTM D1525
Tensile Strength at Break	48	MPa	-----	ASTM D638
Elonation at Break	1	%	-----	ASTM D638
Tensile Modulus	3200	MPa	-----	ASTM D638

- Manufacturer: Tabriz Pet.co.
- Application: insulation board(xps), foam sheet of food & fruits trays.
- Process: Extrusion, Injection Molding.
- Features: Good flowability.

PETRO BAMDAD AZARAN
ENGINEERING & TRADING CO

Add: No.148, Motahari St., Tehran, Iran -- Tel: +98 21 87700799 -- Email/Web:
info@petrobam.com/www.petrobam.com